

**EASY TO
INSTALL
CONFIGURE
CODE**



FAST AND EASY HIGH RESOLUTION PRINTER

PRINTHEAD

From 1mm to 25.4mm

HIGH SPEED PRINTING

Up to 120m/min 300dpi

EASY TO USE

5" touchscreen with intuitive interface for easy configuration

10 REASONS

1. No filter change required
2. Low cost printer
3. Small size
4. Easy use and messages creation
5. No maintenance required
6. No expendable parts
7. High resolution printing
8. Inks without hazardous solvent
9. Multi-material printing
10. High profitability printer



VERSATILE SOLUTIONS

High resolution printing at high speed

HIGH QUALITY

Texts, logos, barcodes, QR codes and high density pictures

EFFICIENT AND FLEXIBLE

Database compatible to suit any type of industrial application

VARIABLE PRINT CONTROL

150dpi / 300dpi / 600dpi print resolution for optimal printing

ROBUSTNESS

Suitable for any type of environment (whether wet, dusty, corrosive...)

QUICK SETUP

Fast and intuitive parameters setting

SAFE OPERATION

Easy configuration of safety parameters

PROFITABILITY OF PRINTING COSTS

Cost per print calculator

Bulk system installation possible to save on printing costs

EASY PRINTING AT LOW COST

THE ONLY MANUFACTURER TO OFFER



TECHNICAL SPECIFICATIONS PRINTER TIJ 2.5

K125NF

PRINTERS

- Steel housings and compact design
- LINUX operating system
- Solid-state electronics with military-grade resistance and non-moving parts
- CPU equipped with anti-interference system
- 5" touchscreen interface
- WYSIWYG templates and printing review
- Menu-driven configuration of safety parameters
- One USB port and one RS-232/RJ45 port
- Encoder and sensor input
- Input: AC 100-240V 50-60Hz
- Output: DC 12.6V 3A
- Operating temperature: 0-55°C
- Water-based inks: 10-40°C
- Polymeric inks: 15-35°C
- Humidity 30 - 70% (without condensation)
- Multilanguage
- Controller dimensions: 136mm x 85mm x 60mm
- Printhead dimensions: 110mm x 80mm x 102mm
- Weight: 430g.



Printer equipped with surge, cross-talk and harmonic filters



Solid-state electronic boards
Military-grade resistance



LINE SPEED AND PRINT RESOLUTION


- Max. print speed: 300m/min
- Max. print resolution: 600dpi

PRINTING FEATURES

- Static text, user inserts, date / time, shift codes, counters and variable data
- TrueType Windows fonts
- Barcode: Codabar, Code128, Code39, Code93, EAN8, EAN13, EAN128, Pharmacode, Plessey, UPC-A,...
- 2D barcode: Datamatrix, QR code, MicroQR, Maxicode,...

PRINthead

- TIJ 2.5 technology
- Printing distance 2-6mm
- Cartridge parameters and ink levels managed by RFID recognition



WIDE RANGE OF INKS

Polymeric for non-porous materials.
Water-based for porous and semi-porous materials
Food dye, pigmented, invisible, UV
Wide range of colors
High adherence and long decap



Industrial coding and marking printers

www.tidirefi.com

📍 Calle Majuelo 5,
Pol. Ind. Cantabria I,
26009 Logroño (La Rioja)
Spain
☎ Telf: +34 941 265 066
✉ info@tidirefi.com

